

PAL Pro 43 SERIES MECHANICS PACKAGE



CHASSIS: 2015 Ford F-550, 4x4, Regular Cab, Automatic 1FDUF5HT6FEA77541

Palfinger model PCB43-11CS Crane body as follows:

- 11' long heavy duty galvanealed steel body
 - 14" double panel slam type tailgate
 - 21" workbench bumper with through compartment and flexible step
 - 5/16" top plate bumper with integrated 2" receiver tube hitch
 - 44" sidepicks with curbside 1st and 2nd compartments raised to 60" to allow for oxygen and acetylene bottles
 - Sealed automotive style wiring harness with easy access power distribution panel
 - FMVSS 108 LED light and reflector kit
 - Strip lighting in all compartments
 - (2) Work lights on rear of body with wiring harness for up to an additional (4) work lights
 - Entire body E-coat primed in 12 step process
 - Compartment interiors painted with multicolor spray finish
 - Understructure and bottom of compartments undercoated
- Shelving arrangement as follows:
- Streetside front vertical compartment- C-Tech 9 drawer cabinet
 - Streetside second vertical compartment- (2) Adjustable divider trays.
 - Streetside horizontal compartment- (1) Adjustable shelf and (1) 20"L x 8"H x 13"D Book rack
 - Streetside rear vertical compartment- (2) Adjustable divider trays
 - Curbside front vertical compartment- Vented compartment with oxygen and acetylene tank holders
 - 60" high interior partition kit with (3) Adjustable shelves
 - Curbside second vertical compartment- (2) Adjustable divider trays
 - Curbside horizontal compartment- (1) Adjustable divider tray
 - Curbside rear vertical compartment- (1) Hose reel mounting shelf
 - Reinforce spring pack on rear axle to level truck

- Spray in bed liner on compartment backs, tops, cargo floor, inside tailgate and workbench bumper
- ICC Safety kit located in cab
- Installed and painted to match cab

Palfinger model PSC4329 telescopic crane as follows:

- 43,000 ft./lb. rating
- 400 degree rotation
- 29' hydraulic reach
- 8,000 lb. maximum lift capacity (Double Line)
- Load holding valves on all cylinders
- Overload protection system
- Anti two block system located on winch in lieu of boom tip
- Radio remote control
- Crane hook and snatch block
- Hexagonal boom
- Boom support
- Power out (crane side only)/Power down outriggers
- Stabilizers on each front corner
- 30 gallon bulkhead mounted oil reservoir

Palfinger model PRC 35 Rotary screw air compressor as follows:

- 35 CFM @ 175 PSI
- Continuous duty cycle
- Integrated hydraulic oil and air coolers
- Hour meter, high temperature and high pressure safety shutdowns
- 1/2" x 50' Air hose reel located in curbside rear vertical compartment and routed through rear wall with guide
- 1/2" moisture separator/regulator/oiler

Crane S/N: 50-200400287

Body S/N: 15-00290

Compressor S/N :800402